



DATA SHEET

Effective November 1, 2011

Product Overview

RockTile is an advanced multi-layer rubber flooring system that addresses all the concerns of a modern rock climbing wall facility. The durable rubber surface is attractive, easy to clean and provides great underfoot stability while walking.

Two thicknesses are available to suit certified fall heights of either 1.8 metres or 2.5 metres. Both tile thicknesses are dual laminate and dual density and come with bevelled edges around the perimeter of the tile.

RockTile comes standard with a black base colour with either red or blue speckles. Other custom colours are available upon request and quotation. Protect-A-Gloss floor finish can be applied after installation to give the surface even more appeal, whilst also assisting with routine cleaning.

Specifications

RockTile Base Layer

Material	Polymerically bound recycled rubber and polystyrene	Thickness	RT70 - 50mm RT100 - 80mm
Density	450kg/m ³	Tolerances	Dimensions - \pm 1.5% Density - \pm 5%
Dimensions	1m x 1m		

RockTile Top Layer

Material	Polymerically bound recycled rubber	Thickness	20mm
Density	700kg/m ³	Tolerances	Dimensions - \pm 1.5% Density - \pm 5%
Dimensions	1m x 1m		
		Colour	Base colour black with either red or blue speckles

- An installation guide is available upon request.

Applications

Modern rock climbing wall facilities.

Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of A1 Rubbers products, are given in good faith, based on A1 Rubbers current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with A1 Rubbers recommendations. The user of the product must test the product's suitability for intended application and purpose. A1 Rubber reserves the right to change the properties and tolerances of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Document No. RTNOV11DATA

QLD

NSW

VIC